

Material Safety Data Sheet (U.S.)

Workplace Hazardous Material Information System (Canada)

Issue Date: 12/01/98; Revisions: Rev 2: 06/13/05; Rev 3: 06/13/08; Rev 4: 11/23/11; Rev 5: 05/29/12

Lead/Acid Storage Battery


Product Name: Lead / Acid Storage Battery

Section I: Manufacturer's Name and Contact Information

Product Information: (270) 866-6056 Transportation Emergency Phone:
Manufacturer: Superior Battery Mfg Co, Inc CHEMTREC 1-800-424-9300
P. O. Box 1010; 2515 Hwy 910 (24 hours, during transportation only)
Russell Springs, KY 42642
Fax: (270) 866-6066 email: sales@superiorbattery.com

Section II: Hazardous Ingredients/Identity Information

Common name: Lead / Acid Storage Battery
Chemical Family: Toxic and Corrosive Material Mixture
Synonyms: SLI Battery
CAS No.: Mixture
D. O. T. Hazard Class: Corrosive Material
Shipping: New batteries and batteries shipped for recycling have the same DOT, IATA and IMO descriptions:
Ground – USDOT, CAN-TDG Battery, wet, filled with acid, hazard class 8, UN 2794, PG III, Corrosive or Battery, wet, non-spillable, hazard class 8, UN 2800, PG III, Corrosive or Battery, dry, UN #: N.A..
International Maritime Organization IMO: Batteries, wet, fill with acid, electric storage, IMO Class 8, UN2794 or Batteries, wet, non-spillable, electric storage, IMO Class 8, UN2800
Cracked or leaking batteries being recycled must be stored and shipped in a container that is sturdy, acid resistant, leak proof and kept closed. Transport requirements vary by state.
ICAO-IATA Air transport:
Battery, wet, filled with acid, hazard class 8, UN 2794, PG II, Corrosive Reference IATA Packing instructions 800
IMO-IMDG Vessel: Battery, wet, filled with acid, hazard class 8, UN 2794, PG II, Corrosive Reference IMDG packing instructions P801



Ingredient/ CAS Number	Max %	SARA applies			Air contaminant levels	
		302	311/312	313	ACGIH//TLV (mg/m ³)	OSHA PEL (mg/m ³)
Water, plastic and carbon	Balance					
Lead, inorganic (CAS#: 7439-92-1) Lead Oxide (CAS#: 1309-60-0) Lead Sulfate (CAS#: 7446-14-2)	60 % (wet battery) 95 % (dry battery)	NA	Y	Y	0.05	0.05
Sulfuric Acid (CAS#: 7664-93-9)	10 - 30% wet < 1 % dry	Y RQ: 1000 lbs	Y	*	0.2	1.0
Antimony (CAS: 7440-36-0)	1 - 6	NA	Y	Y	0.5	0.5
Arsenic (CAS#: 7440-38-2)	<0.1	NA	Y	Y	0.01	0.01

* Only sulfuric acid aerosols are reportable. These include mists, vapors, gas, fog, and other airborne forms of any particle size. All ingredients are listed with EPA TSCA Inventory of Chemical Substances.

Section III: Physical/Chemical Characteristics

	Lead	Electrolyte	Hydrogen	Plastic/ Battery case
Boiling Point	1755 °C	95 °C	-252 °C	
Vapor Pressure		~ 1mm Hg		
Vapor Density (Air = 1)		~3.4	~ 0.07	
Melting Point	327.4 °C		-259 °C	Polypropylene: >160 °C

Superior Battery Mfg Co, Inc

P. O. Box 1010

2515 Hwy 910

Russell Springs, KY 42642

Phone: (270) 866-6056

Fax: (270) 866-6066!

Material Safety Data Sheet (U.S.)

Workplace Hazardous Material Information System (Canada)

Issue Date: 12/01/98; Revisions: Rev 2: 06/13/05; Rev 3: 06/13/08; Rev 4: 11/23/11; Rev 5: 05/29/12

Lead/Acid Storage Battery

Specific Gravity (H ₂ O = 1)		1.21 – 1.3		
Evaporation Rate	Not determined			
Solubility in Water		100 %		
Appearance and Odor:	Acid saturated lead oxide is dark reddish-brown to gray solid with acidic odor.	Oily colorless liquid, characteristic acid odor when hot or charging.	Colorless, odorless gas.	Solid
pH:		<1		

Section IV: Fire and Explosion Hazard Data

Flash Point (method used): NA

Flammable Limits: Lead acid batteries will not burn or will burn with difficulty. Hydrogen gas is generated during charging and may be flammable and explosive when mixed with oxygen, air or chlorine.

Hydrogen LEL: 4 %; UEL: 74.2 %

Extinguishing Media: Halon, dry chemical, foam or CO₂. Cool exterior of batteries exposed to fire to prevent ruptures.

Unusual Hazards: Hydrogen and oxygen gases are generated in the cells during normal battery operations. These gases enter the air through the vent caps. Keep ignition sources away from the battery. Sulfuric acid mist and vapors generated by battery overcharge, heat or fire are corrosive. Ensure proper ventilation of charging areas consistent with OSHA (CFR 1910 and 1926), National Fire Code, Building Code and other relevant standards. !

Special Fire Fighting Procedures: Use positive pressure, self-contained breathing apparatus and protective clothing. Extinguish fire with material suitable for surrounding combustible materials.

Section V: Reactivity Data

◆ **Stable** **Unstable:**

!

◆ **Conditions to Avoid:** Avoid overcharging battery. Do not allow smoking, open flame or sparks near batteries while charging. Avoid high temperature. Battery electrolyte will react with water and produce heat. Keep battery case away from strong oxidizers.

!

◆ **Incompatibility:** Lead/lead compounds: potassium, carbides, peroxides, phosphorus, sulfur. Battery electrolyte: strong reducing agents, combustible and organic materials, most metals, nitrates, chlorates, chlorides. Battery case: strong oxidizing agents. Short circuits may result in fire.

◆ **Hazardous Decomposition/ Byproducts:** An explosive hydrogen and oxygen mixture within the battery may be generated during charging. See further section VI. Sanding and grinding of battery posts, post building and connector burning activities will release airborne lead.

◆ **Hazardous Polymerization:** Will not occur

Section VI: Health Hazard Data

Under normal conditions of battery use, battery materials will not present a health hazard.

- ◆ **Routes of entry:** Ingestion: possible via hand contaminated by contact with lead or acid components of the battery. Inhalation: acid mist generated during battery charge may cause respiratory irritation. Eye contact: possible if the battery electrolyte is splashed. Skin Contact: possible. Skin absorption is not a significant route of entry. Battery electrolyte is corrosive to skin.
- ◆ **Acute Health Effect:** Overexposure to lead compounds may cause upset stomach, loss of appetite, sleeplessness, and fatigue. Contact with battery electrolyte (acid) may irritate the skin. Battery electrolyte may cause corneal damage of the eyes or irritation of the mucous membranes and/or inflammation of the upper respiratory system.
- ◆ **Chronic Health Effects** Lead compounds may cause chronic anemia, kidney and nervous system damage. Lead may also cause reproductive system damage. Repeated contact with battery electrolyte may lead to irritation of the skin and may result in dermatitis. Battery electrolyte may scar the cornea, causing blindness, and cause chronic bronchitis. Prolonged contact to acid vapor may cause erosion of tooth enamel.
- ◆ **Carcinogenicity:** The **IARC** has classified strong inorganic acid mists containing sulfuric acid as a Category 1 carcinogen, a substance that is carcinogenic to humans. The **AGGIH** has classified "strong inorganic acid mist containing sulfuric acid" as an A2, suspected human carcinogen. These classifications do not apply to liquid forms of sulfuric acid or electrolyte contained within the battery. Under normal battery use, sulfuric acid mist is not generated.

Material Safety Data Sheet (U.S.)

Page 3 of 4

Workplace Hazardous Material Information System (Canada)

Issue Date: 12/01/98; Revisions: Rev 2: 06/13/05; Rev 3: 06/13/08; Rev 4: 11/23/11; Rev 5: 05/29/12

Lead/Acid Storage Battery

NTP and IARC have classified lead as an animal carcinogen (A3). While the lead is carcinogenic in experimental animals at relatively high doses, lead is unlikely cause cancer in humans except under uncommonly high levels of exposure.

- ◆ **Signs/Symptoms of Exposure:** Under normal battery use, the components do not present a health hazard. Under abnormal conditions or in case of fire, breakage or overcharge, battery can cause the following symptoms:
SKIN: Irritation or skin burn. EYES: Burning. INGESTION: upset stomach, fatigue, irritation or burns in the mouth and the gastrointestinal system. INHALATION: Breathing the acid vapor may cause respiratory difficulties.
- ◆ **Emergency and First Aid:**
SKIN: Remove from source. Wash thoroughly with soap and water. Treat as acid burn. If battery electrolyte is splashed in shoes, remove immediately and discard. Remove contaminated clothing and obtain medical attention.
EYES: Flush thoroughly with cool water for 15 minutes, lifting lids. Get medical attention. Treat as an acid burn.
INHALATION: Remove to ventilated area. Get medical attention.
INGESTION: Lead/lead compounds: consult physician. Battery Electrolyte: Do not induce vomiting, keep quiet, get medical attention immediately.
- ◆ **Medical Condition Generally Aggravated by Exposure:** Lead and its compounds can cause chronic liver, kidney and neurological problems. Contact with battery electrolyte may cause dermatitis or eczema of the skin. Sulfuric acid mist may irritate the respiratory system.

Section VII: Precautions for Safe Handling and Use

- ◆ Steps to be Taken in Case Material is Released or Spilled: Stop leak at source. Ventilate the area. Remove combustible material and all sources of ignition. Wear protective clothing, acid resistant boots and gloves, face shield and goggles. Segregate the spill and neutralize with baking soda, soda ash, lime or use an appropriate acid absorbent. Collect residue in an approved container. Do not release to streams, lakes, sewer, etc.
- ◆ Waste Disposal Method: Return spent batteries to distributor, manufacturer or lead recycler. Neutralize acid spill or use proper absorbent and place waste in proper container. Cracked or leaking batteries being recycled must be stored and shipped in a container that is sturdy, acid resistant, leak proof and kept closed. Dispose of batteries and components according to all local, state and federal regulations. Some states regulate leaking batteries as hazardous waste, classification D002 (corrosive) and D008 (lead) even when recycled. Check with state authorities.

Section VIII: Control Measures

- ◆ Respiratory Protection: None required under normal handling conditions. During battery formation or recharge, acid mist may be generated. If irritation occurs use a suitable respirator for protection.
- ◆ Ventilation: Store lead acid batteries in cool, dry and properly ventilated area. Never recharge batteries in a closed, unventilated area.
- ◆ Protective Gloves: Acid resistant rubber or plastic gloves.
- ◆ Eye Protection: Wear chemical safety goggles or face-shield during non-routine tasks, including battery maintenance.
- ◆ Other Protective Clothing or Equipment: Eye wash and safety shower installed near to storage or charging area, safety shoes with rubber or neoprene boots and aprons.
- ◆ Work/Hygienic Practices: Make sure vent caps are tight. Do not smoke or use open flames in charging area. Wash your skin thoroughly after handling battery. Discard contaminated clothing according to state or EPA regulations.

Storage Requirements: Store lead acid batteries in cool, dry and properly ventilated area. Make sure vent caps are in place. Keep the batteries from extreme heat or freezing. Place a minimum of two layers of corrugated cardboard between battery layers for storage. Protect terminals to prevent short circuits. Keep out of reach of children.

Section IX: Battery Recycling

Battery recycling

It is illegal to discard batteries in the trash. State laws require batteries to be recycled by a permitted recycling facility. Batteries should be returned to the manufacturer or distributor for recycling, or directly to a permitted recycling facility.

Packaging of spent batteries for recycling:

1. Recycle batteries should be palletized.
2. Heavier batteries are on bottom layer on pallet.
3. Arrange layers to avoid pallet overhang.
4. Minimum of two (2) sheets of corrugated cardboard between layers or one (1) honeycomb layer sheet.
5. Keep battery layers reasonably flat for top loading.
6. Limit each pallet to three (3) layers of batteries.
7. Keep battery terminals aligned to prevent short circuits; no side terminal contact. No exposed terminals.
8. Stretch wrap or banding is mandatory. No steel strapping.
9. Used batteries must be protected from weather in storage.

Material Safety Data Sheet (U.S.)

Workplace Hazardous Material Information System (Canada)

Issue Date: 12/01/98; Revisions: Rev 2: 06/13/05; Rev 3: 06/13/08; Rev 4: 11/23/11; Rev 5: 05/29/12

Lead/Acid Storage Battery

Section X: Regulatory Information

RCRA (Lists of Hazardous Wastes, 40 CFR 261 Subpart D):	Components present in this product at a level which could require reporting are Arsenic: D004 Sulfuric Acid: D002 Lead: D008
CLEAN AIR ACT (SEC. 112. Hazardous Air Pollutants):	Components present in this product at a level which could require reporting are: Antimony compounds; Arsenic compounds; Lead compounds Lead Sulfate: 10 lbs (4.54 kg) Sulfuric acid: 1,000 lbs (454 kg)
CLEAN WATER ACT (RQ, 40 CFR):	
CERCLA: Section 102 (RQ, 40 CFR Part 302):	Components present in this product at a level which could require reporting are: Antimony: 5,000 lbs (2270 kg) Arsenic: 1 lb (0.454 kg) Lead: 10 lbs (4.54 kg) Lead Sulfate: 10 lbs (4.54 kg) Sulfuric acid: 1,000 lbs (454 kg)
SARA Title III: Section 302 -304, 40 CFR 355	Components present in this product at a level which could require reporting are: Sulfuric acid: 1,000 lbs (454 kg)
Section 311 - 312:	Components present in this product at a level which could require reporting are: Antimony: 5,000 lbs (2270 kg) Arsenic: 1 lbs (0.454 kg) Lead: 10 lbs (4.54 kg) Lead Sulfate: 10 lbs (4.54 kg) Sulfuric acid: 1,000 lbs (454 kg).
Section 313:	Components present in this product at a level which could require reporting are: Antimony, Arsenic, Lead, Lead Compounds, Sulfuric acid aerosols
TSCA Section 8(b) Inventory Status:	All ingredients are listed on TSCA Inventory of Chemical Substances or exempt from TSCA Inventory requirements.
Workplace Hazardous Materials Information System (WHMIS):	Arsenic: D1A; D2A Lead: D2A Lead Oxide: C; D2A Lead Sulfate: D2A Sulfuric acid: D1A; E

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

State Lists

California Proposition 65:

Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals (arsenic) and Strong inorganic acid mists including sulfuric acid known to the State of California to cause cancer. Wash hands after handling.

Antimony	- CA, FL, MA, NJ, PA
Arsenic	- CA, FL, MA, NJ, PA
Lead	- CA, FL, MA, NJ, PA
Lead Oxide	- CA, FL, MA, NJ, PA
Lead Sulfate	- CA, FL, MA, NJ, PA
Sulfuric acid	- CA, FL, MA, NJ, PA

Disclaimer: "The information and recommendations presented herein are based on sources believed to be reliable as of the date hereof. Superior Battery Mfg. Co., Inc. makes no representation as to the completeness or accuracy thereof. It is the user's responsibility to determine the product's suitability for its intended use, the product's safe use, and the product's proper disposal. No representations or warranties not expressly set forth herein are made hereunder, whether express or implied by operation of law or otherwise, including, but not limited to any implied warranties of MERCHANTABILITY OR FITNESS. Superior Battery Mfg. Co., Inc. neither assumes or authorizes any other person to assume for it, any other or ADDITIONAL LIABILITY OR RESPONSIBILITY resulting from the use of, or reliance upon, this information."

Copyright © 1998, 2005, 2008, 2011, 2012 Superior Battery Mfg Co, Inc.

Superior Battery Mfg Co, Inc

P. O. Box 1010

2515 Hwy 910

Russell Springs, KY 42642

Phone: (270) 866-6056

Fax: (270) 866-6066!